Wollongong Wastewater Treatment Plant July Pollution Monitoring Summary



EPL 218

Summary period: 01-07-2021 to 31-07-2021 Licensee: Sydney Water Corporation

Date obtained: 04-08-2021 PO Box 399

Date published: 18-08-2021 PARRAMATTA NSW 2124

Table 1: 3 Day Geometric Mean data

EPA Point 5 Site code WO0005	Point description: At the inlet to the effluent pumping station							
pollutant	unit of measure	sampling frequency	3DGM limit	3DGM Actual	within limits			
total suspended solids	mg/L	monthly	50	<2	yes			

3 Day Geometric Mean (3DGM) is a way to average a set of values and is commonly used with water quality assessments which show a great deal of variability. 3DGM is calculated by multiplying the results of the analysis of three samples collected on three consecutive days and then taking the cubed root of that amount.

Table 2: Routine monitoring data

EPA Point 5 Site code WO0005	Point description: At the inlet to the effluent pumping station						
pollutant	unit of measure	sampling frequency	number of samples	minimum result	mean result	maximum result	
aluminium	ug/L	monthly	1	_	_	21	
biochemical oxygen demand	mg/L	every 6 days	5	4	5.2	8	
carbonaceous biochemical oxygen demand	mg/L	every 6 days	5	<2	<2	4	
copper	ug/L	monthly	1	-	_	2.4	
diazinon	ug/L	monthly	1	-	_	<0.1	
hydrogen sulphide (unionised)	ug/L	monthly	1	-	_	<30	
total suspended solids	mg/L	every 6 days	5	<2	<2	<2	

Average and percentile limits are only applied annually for routine monitoring data in Table 2.

Effluent quality monitoring results obtained from EPA Point 5 are used to indicate the quality of water discharged at EPA Point 1 (discharge to waters).